

SAFETY DATA SHEET

Complies with OSHA HCS 29 CFR 1910.1200, including appendix D, and UN GHS for classification and labeling.

SECTION 1: IDENTIFICATION

COMPANY: Total Wall, Inc.
ADDRESS: 390 Viking Circle

Rio, WI 53960

EMERGENCY PHONE NUMBER: 888-702-9915
Total Stop RA

PRODUCT IDENTIFIER: Total Stop RA (all textures and grades)

PRODUCT USE: Liquid-applied moisture barrier/adhesive

EFFECTIVE DATE: 06/2016
REVISION NUMBER: Initial issue

SECTION 2: HAZARD(S) IDENTIFICATION

Caution! Eye, skin and respiratory irritant



Routes of exposure: Eyes, skin, ingestion, inhalation.

Skin Contact: May be irritating to skin. Skin Absorption: No known hazards.

Eyes: Damaging to the eyes.

HEALTH 1

FLAMMABILITY 0

REACTIVITY 0

PERSONAL PROTECTION B

Inhalation: Inhalation of mist may cause irritation to the respiratory tract.

Ingestion: May be harmful if swallowed. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.



SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	percent by weight
Acrylic resin emulsion blend	proprietary	40
Calcium carbonate	471-34-1	35
Water	7732-18-5	10
Titanium dioxide	13463-67-7	10
Carboxylate thickener	proprietary	2
Antifoam	64741-88-4	1-2
Coalescent	111-76-2	1
Preservative	64359-81-5	< 0.1
Ammonia (to adjust pH)	1336-21-6	< 0.1

SECTION 4: FIRST AID MEASURES

Skin Contact: Wash exposed area with a soap solution or water and remove contaminated clothing.

Eye Contact: Immediately flush eyes with water for 15 minutes. Remove contact lenses if it can be done easily. Immediately contact a physician for additional treatment.

Inhalation Exposure: Remove victim from contaminated area to fresh air. Apply appropriate first aid treatment as necessary.

Ingestion: Do not feed anything by mouth to an unconscious or convulsive victim.

Specific: Do not induce vomiting. Immediately contact a physician. Dilute contents of stomach using 3-4 glasses of milk or water.



SECTION 5: FIRE-FIGHTING MEASURES

Not Flammable Flash point: N/A

Flammable limits: N/A

Auto-ignition Temperature: None

Extinguishing media: N/A

Special Fire Fighting Procedures: None Special Fire Fighting Equipment: None Unusual Fire and Explosion Hazards: None Explosion Data: Not an explosion hazard. Hazardous Decomposition Products: None



SECTION 6: ACCIDENTAL RELEASE MEASURES

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Prevent further leakage or spillage if safe to do so.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways. Methods for containment: Absorb spills with an inert absorbent material such as soil, kitty litter, sand or Oil-dri. After absorbing spill with inert material, place in a chemical waste container.

Methods for cleanup: Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section.

SECTION 7: HANDLING AND STORAGE -

Storage Instructions: Keep container tightly closed when not in use. Store indoors or under cover in a dry environment in temperatures between 40 F and 115 F, and out of reach of children and pets.

Handling Instructions: Handle in accordance with good industrial hygiene, normal chemical handling and safety practices. Wash after handling.



SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	CAS No.	ACGIH and OSHA
calcium carbonate	471-34-1	5 mg/ $M^3 * TLV$
coalescent (glycol ether)	111-76-2	20 ppm TWA
titanium dioxide	13463-67-7	5 $mg/M^3 * TLV$
antifoam	64741-88-4	$5 \text{ mg/M}^3 * \text{TLV}$
ammonia	1336-21-6	25 ppm PEL
		* Note as respirable dust (or mist

^{*} Note - as respirable dust (or mist).

Use appropriate engineering controls, such as providing good general ventilation, to control airborne levels below recommended exposure limits.

Ventilation Protection: Adequate ventilation.

Recommended Respiratory Protection: If ventilation is inadequate, use a mask with dust/mist/fume cartridges.

Recommended Skin Protection: Rubber gloves.

Other Protective Equipment: Full coveralls.

Recommended Eye Protection: Splash proof chemical goggles

Personal Hygiene: Wash thoroughly after handling product

TOTAL WALL

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Thixotropic, opaque liquid, 30,000 cps viscosity

pH: Approx. 9.2

Flash Point: Non-flammable

Vapor Pressure: 17 mm Hg

Vapor density: 1 (water = 1)

Evap. Rate: < 1 (ether = 1)

Percent volatile by volume: Approx. 43%

VOC: Approximately 17.5 gm/L

Sp. Gr. 1.1

% Solubility (water): Dispersible in water (partially soluble).

Odor: Mild

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under recommended handling and storage conditions. Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: Extreme heat, freezing temperatures and incompatible materials. Incompatible Materials: Water reactive materials.

Special Decomposition Products: Forced thermal decomposition may release irritant fumes and toxic gases.



SECTION 11: TOXICOLOGICAL INFORMATION

The below data is obtained from NIOSH (National Institute for Occupational Safety and Health) listing of RTECS (Registry of Toxic Effects of Chemical Substances).

Calcium Carbonate: RTECS Number: EV9580000

Inhalation: Rat TCLo - Lowest published toxic concentration:

250 mg/m3/2H/24W (Intermittent) Lungs, Thorax, or Respiration - Fibrosis, focal Inhalation - Rat TCLo - Lowest published toxic concentration : 84 mg/m3/4H/40W

(Intermittent) Lungs, Thorax, or Respiration - Fibrosis (interstitial) Liver - Other changes: Kidney/Ureter/Bladder

Titanium Oxide: RTECS Number: XR2275000

Inhalation: Rat TCLo - Lowest published toxic concentration: 1 mg/kg

Lungs, Thorax, or Respiration - Other changes: Biochemical - Metabolism (intermediary)

- Effect on inflammation or mediation of inflammation

Ingestion: Oral - Rat TDLo - Lowest published toxic dose : 60 gm/kg Gastrointestinal

- Hypermotility, diarrhea Gastrointestinal - Other changes

Chronic Effects: Normal application procedures for this product pose no hazard as to the release of respirable titanium dioxide dust, but grinding or sanding dried films of this product may yield some respirable titanium dioxide.

2-butoxy ethanol (glycol ether): RTECS Number: KJ857500 Inhalation:

200 ppm; fertility and reproductive effects.

Ingestion: 720 mg/Kg; developmental abnormalities. RTECS

listed carcinogen.

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name IARC * OSHA Carcinogen

Titanium dioxide 2B - Possible Human Carcinogen Listed

Although IARC (International Agency for Research on Cancer) has classified titanium dioxide as possibly carcinogenic
to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use
of products in which titanium dioxide is bound to other materials, such as paint."

SECTION 12: ECOLOGICAL INFORMATION

Aquatic toxicity is not known. Product is mildly alkaline, therefore higher concentrations of the product in estuaries may increase the pH of the estuary slightly.

The calcium carbonate component is not highly mobile in the soil. This component is natural to the environment and presents no foreseeable negative impact. The water-based polymer component is not toxic and is long term biodegradable. The polymer is highly mobile in the soil until it cures, and then it is not mobile in the soil.

There is no known data on the cumulative ecological effects of the minor and trace components, which include the antifoam and coalescent. However, it is believed these components are at least partially degradable.

SECTION 13: DISPOSAL CONSIDERATIONS

Arrange for disposal in accordance with Federal, state and local guidelines. Triple-rinse container prior to offering for recycle, reconditioning or disposal.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.
DOT Hazard Class: Non regulated.
IMDG UN Number: Non regulated.
IATA Shipping Name: Non regulated.



SAFETY DATA SHEET

SECTION 15: REGULATORY INFORMATION

SARA: This product does not contain any chemicals which are subject to the reporting requirements of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372).

California Proposition 65: This product contains a material, calcium carbonate, known to the state of California to cause cancer or reproductive harm.

This product contains Titanium Dioxide, and is listed by Massachusetts, New Jersey and Pennsylvania Right-to-Know laws.

Canada WHMIS: Xi - Irritant

EU Class: Irritant, in accordance with CLP Regulation (EC) No 1272/2008 on the classification, labeling and packaging of substances and mixtures.

SECTION 16: OTHER INFORMATION

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Prepared By: Technical Department

Total Wall, Inc.

390 Viking Circle


Rio, WI 53960

888-702-9915

Initial Issue Date: June 1, 2016

Revision Date: No revisions

Revision Summary: Not available



NFPA Legend



SAFETY DATA SHEET

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Individuals and employers should use this information only as a supplement to other information gathered by themselves and must make independent determination of suitability and agreement of information from all sources to assure proper use of these materials and the safety and health of individuals. This should be done in advance of need. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state/provincial, and local laws and regulations.

End of Document